



EL1SS

## Simplicity. Durability. Exceptional Value.

The **EL1SS** Telephone Intercom and Access Control System provides wired telephone intercom communication and secure access control at the gate or door. It is easy to install, and its rugged stainless steel housing provides reliable, durable performance year after year—at a price everyone can afford. With the EL1SS, residents or small businesses can simply communicate with visitors and grant or deny access, all from the convenience of their phone.

### TOP 5 FEATURES

- Call forwarding
- Call waiting
- Party mode to keep the entrance open
- “Do not disturb” mode for added privacy
- Auto-call feature that enables immediate notification when a guest pulls up to the gate (requires optional presence sensor)

### ADDITIONAL FEATURES

- Easy to program from the keypad—no software needed
- Connects directly to an existing residential home phone line; no additional monthly expenses are incurred
- Designed with a hinged faceplate that saves an average of 10 minutes on installation time
- Intercom mode allows for communication between the unit and a resident’s phone without the expense of paid telephone service
- Compatible with DSL phone lines

# EL1SS



FEATURE	EL1SS
<b>SYSTEM FEATURES</b>	
Entry Codes	200 (4-digit) unique programmable entry codes
Voice Communication	Intercom/POTS/DSL
Audio Circuit	Full duplex voice communication
Software	None needed
Auto-Call	Enables immediate notification when a guest pulls up to the gate (requires optional presence sensor)
Intercom Mode	Yes
Unique Ringing	Yes
Call Waiting	Yes
Call Forwarding	Yes (telco mode only)
“Do Not Disturb” Mode	Yes
Party Mode	Yes (holds open entryway)
Vacation Mode	Yes
Temporary (1-Time) Entry Code	Yes
<b>BASIC INPUT/OUTPUT</b>	
Gates/Doors of Control	2
<b>PANEL</b>	
Faceplate	Brushed stainless steel with green backlit metal keypad and illuminated call button
Rear Housing	Black powder-coated stainless steel
Mounting Options	Surface/gooseneck
Power Supply	120VAC to 16VDC transformer (included)
Bypass Board	Included; allows unit to be disconnected without interrupting normal telephone operation
Temperature Range	-4°F (-20°C) to 149°F (65°C)
Height	6.25 in.
Width	10 in.
Depth	5.25 in.
Regulatory	FCC Part 15, FCC Part 68, Industry Canada IC compliant
Weatherization	NEMA 3R
Warranty	2 Years

## OPTIONAL ACCESSORIES



### Gooseneck Pedestal (PED42)

42 in. pad-mount pedestal, 2 x 2 in. square pipe with a black powder-coated finish, 11-gauge steel.



### Gooseneck Pedestal (PED64)

64 in. in-ground mount pedestal, 2 x 2 in. square pipe with a black powder-coated finish, 11-gauge steel.

Learn more at [LiftMaster.com/AccessControl](http://LiftMaster.com/AccessControl)

Sales Support: 800.282.6225

Technical Support Center: 800.528.2806

[LiftMasterDealer.CustHelp.com/App/Ask](http://LiftMasterDealer.CustHelp.com/App/Ask)