

M K 5 0 0 G S

# MINIKEY ACCESS CONTROL SYSTEM

Self-Contained Keypad System for Door and Gated Entrances.



## KEY FEATURE

### STAND-ALONE ACCESS SYSTEM

Compact for easy installation

## SMART

**GREATER CONTROL AT THE SITE** WITH TWO RELAYS THAT CAN BE CONTROLLED INDIVIDUALLY OR TOGETHER.

**INCREASED CONVENIENCE** WITH CODES THAT CAN BE PROGRAMMED USING 4 OR 5 DIGITS AND ACTIVATE ONE OR BOTH RELAYS.

**STORES DATABASE INFORMATION IN MEMORY** WHEN THE POWER GOES OUT, ENSURING IMMEDIATE STARTUP AND OPERATION WHEN POWER IS RESTORED.

## RELIABLE

**ENGINEERED TO BE WEATHER-RESISTANT AND HIGHLY VANDAL-RESISTANT** WITH A WELL-CRAFTED LOOK FOR INTERIOR OR EXTERIOR USE.

**EXCELLENT VISIBILITY DAY OR NIGHT** WITH RECESSED SIDE-LIT METAL KEYPAD.

## SECURE

**PREVENTS UNAUTHORIZED ENTRY** BY DISABLING KEYPAD FOR 3 MINUTES IF AN UNAUTHORIZED USER HAS ATTEMPTED TOO MANY INCORRECT ENTRY CODES. THE SYSTEM CAN BE PROGRAMMED TO PERMIT FROM 1 TO 10 ATTEMPTS PRIOR TO ENGAGING THE LOCKOUT.

## TOTAL SOLUTION ACCESSORIES:

### GOOSENECK PEDESTAL

42 in. pad mount or 64 in. in-ground pedestal 2x2 in. square pipe, black powdered coat finish 11 ga. Steel.



PED42 / PED64

### LIFTMASTER ELITE SERIES®

Maglock 12/24VDC with Junction Box features 1,300 lbs. holding force.



MG1300

## MASTERFUL ENGINEERING.

### CAPABILITIES



- 500 Entry Codes
- Variable Entry Code Length – can be programmed using 4 or 5 digits and can activate a single relay or both relays.
- Two Relays, one for the main unit and one auxiliary relay to support status inputs up to 500 feet from the main unit.
- Relays can be controlled individually or together.
- Programmable Relay Times – each relay may be programmed independently to activate from 2 to 255 seconds.
- Time Clock Input feature makes it possible to use a dealer-supplied time clock to prevent entry to the facility at a specified time.
- Lightning Protection – inputs and power connections contain some protection against typical voltage spikes. However, in an area where lightning is prevalent, external surge suppressors should be used to minimize damage to the system.

### POWER



- 12VAC or 13.5VDC

## STANDARD SPECS.

#### WARRANTY

- 1-Year Limited

#### RELAYS

- (1) Main Unit
- (1) Auxiliary



3.5"

4.5"

4.5"

### MECHANICS



- Grained Stainless Steel - Surface Mount

### DIMENSIONS



- Surface Mount:  
4.5" W x 4.5" H x 3.5" D

## SHIPPING.

#### SHIPPING WEIGHT (in lbs.)



#### CARTON (1)

- 12.25" W x 11.12" H x 7.5" D
- Keypad System
- Power Supply
- Instruction Manual

For Support Tools and Training Videos, Visit  
[LiftMasterTraining.com](http://LiftMasterTraining.com)

For More Information, Visit  
[LiftMaster.com/AccessControl](http://LiftMaster.com/AccessControl)

Sales Support: **800.282.6225**  
Technical Support Center: **800.528.2806**  
[LiftMasterDealer.CustHelp.com/App/Ask](http://LiftMasterDealer.CustHelp.com/App/Ask)